

# Hip Hop Grill

**LOW VOC** 52" Type II Contract Wallcovering

## Physical Properties

---

Weight	20.0 oz. PLY / 620 G/PLM	13.3 oz. PSY / 451 G/PSM
Backing	Osnaburg	
Width	52" / 132 cm	
Match	Reversible, match	
Repeat	6" H x 5.2" W, half drop	

Meets or exceeds Federal Specification CCC-W-408D for Type II wallcovering

## Fire Safety

---

- Class "A" Fire Rated – Tested in accordance with ASTM E-84 Tunnel test
- Flame Spread 20 / Smoke Developed 45
- Passes NFPA 286 Corner Burn Test

## Environment & Health

---

- Meets California Section 01350 IAQ test requirements for wallcovering
- Can contribute to LEED® EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives
- Can contribute to LEED® MR 5.1 point for regional materials

## Anti-Microbial Features

---

All Symphony® vinyl wallcoverings can be perforated, with a 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates. Symphony® wallcoverings contain anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.

## Warranty

---

5 year warranty against manufacturing defects. Additional information is available at [www.SymphonyWallcovering.com](http://www.SymphonyWallcovering.com)