symphony
CONTRACT WALLCOVERING

Sanshin

LOW VOC 52" Type II Contract Wallcovering

Physical Properties

Weight	20 oz. PLY / 620 G/PLM	13.3 oz. PSY / 451 G/PSM
Backing	Osnaburg	
Width	52" / 132 cm	
Match	Reverse, random	

Custom colors, weights, recycled backing and micro venting available

Meets or exceeds Federal Specification CCC-W-408D for Type II wallcovering

Fire Safety

- Class "A" Fire Rated - Tested in accordance with ASTM E-84 Tunnel Test
- Passes Class "A" NFPA 101 Life Safety Code
- Passes NFPA 286 Corner Burn Test

Environment & Health

- **Contains 10% recycled content**
- **Certified to NSF/ANSI 342 Sustainability Assessment; ask distributor for details**
- **Meets California Section 01350 IAQ test requirements for wallcovering**
- **Can contribute to LEED EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives**
- **Can contribute to LEED MR 5.1 point for regional materials**

Anti-Microbial Features

Symphony® wallcoverings contain antimicrobial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. All Symphony® wallcoverings can be perforated, with a 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

Warranty

5 year warranty against manufacturing defects. Additional information is available at
www.SymphonyWallcovering.com

J. Josephson®, Inc., 35 Horizon Boulevard, South Hackensack, NJ 07606 USA