

Sonnet

LOW VOC 54" Type II Contract Wallcovering

Physical Properties

Weight 20.0 oz. PLY / 619 G/PLM 13.3 oz. PSY / 451 G/PSM
Backing Osnaburg
Width 54" / 137 cm
Match Reverse random match
Repeat N/A

Meets or exceeds Federal Specification CCC-W-408D for Type II wallcovering

Fire Safety

- Class "A" Fire Rated – Tested in accordance with ASTM E-84 Tunnel Test
- Flame Spread 25 / Smoke Developed 45
- Passes NFPA 286 Corner Burn Test

Environment & Health

- Meets California Section 01350 IAQ test requirements for wallcovering
- Can contribute to LEED® EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives
- Can contribute to LEED® MR 5.1 point for regional materials

Anti-Microbial Features

All Symphony wallcovering can be perforated, with a 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

Warranty

5 year warranty against manufacturing defects. Additional information is available at www.SymphonyWallcovering.com