

## Canopy

**LOW VOC**  
52" / TYPE II / 20 oz.

---

### PHYSICAL PROPERTIES

---

**Weight** 20 oz. PLY / 620 G/PLM      13.3 oz. PSY / 451 G/PSM  
**Backing** Osnaburg  
**Width** 52 in. / 132 cm  
**Match** Reverse, random

Meets or exceeds Federal Specification CCC-W-408D for Type II Wallcovering

---

### FIRE SAFETY

---

- Class "A" fire rated - tested in accordance with ASTM E-84 Tunnel Test
- Passes NFPA 286 Corner Burn Test
- Passes Class A NFPA 101 Life Safety Code

---

### ENVIRONMENT & HEALTH

---

- Contains 10% recycled content
- Certified to NSF/ANSI 342 Sustainability Assessment; ask distributor for details
- Meets California Section 01350 IAQ test requirements for wallcovering
- Can contribute to LEED EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives
- Can contribute to LEED MR 5.1 point for regional materials

---

### ANTI-MICROBIAL FEATURES

---

Vycon® wallcoverings contain antimicrobial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. All Vycon® wallcoverings can be perforated, with a 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

---

### CUSTOMS

---

Contact your Vycon distributor for customs.

---

### WARRANTY

---

5 year warranty against manufacturing defects. Additional information is available at:  
**[vyconwallcovering.com](http://vyconwallcovering.com)**

---