

Skyward

LOW VOC
54" / TYPE II / 20 oz.

PHYSICAL PROPERTIES

Weight 20 oz. PLY / 620 G/PLM 13.3 oz. PSY / 451 G/PSM
Backing Osnaburg
Width 54 in. / 137 cm
Match Reverse, random

Meets or exceeds Federal Specification CCC-W-408D for Type II Wallcovering

FIRE SAFETY

- Class "A" fire rated - tested in accordance with ASTM E-84 Tunnel Test
 - Passes NFPA 286 Corner Burn Test
 - Passes Class A NFPA 101 Life Safety Code
-

ENVIRONMENT & HEALTH

- Contains 10% recycled content
 - Certified to NSF/ANSI 342 Sustainability Assessment; ask distributor for details
 - Meets California Section 01350 IAQ test requirements for wallcovering
 - Can contribute to LEED EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives
 - Can contribute to LEED MR 5.1 point for regional materials
-

ANTI-MICROBIAL FEATURES

Vycon® wallcoverings contain antimicrobial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. All Vycon® wallcoverings can be perforated, with a 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

CUSTOMS

Contact your Vycon distributor for customs.

WARRANTY

5 year warranty against manufacturing defects. Additional information is available at:
vyconwallcovering.com
